



(51) International Patent Classification:

C11D 3/20 (2006.01) *C11D 3/40* (2006.01)
C11D 3/33 (2006.01) *C11D 17/00* (2006.01)

(21) International Application Number:

PCT/EP2017/054722

(22) International Filing Date:

1 March 2017 (01.03.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16158180.6 2 March 2016 (02.03.2016) EP

(71) **Applicant** (for all designated States except AE, AG, AU, BB, BH, BN, BW, BZ, CA, CY, EG, GB, GD, GH, GM, IE, IL, IN, KE, KN, KW, LC, LK, LS, MT, MW, MY, NA, NG, NZ, OM, PG, QA, RW, SA, SC, SD, SG, SL, SZ, TT, TZ, UG, US, VC, ZA, ZM, ZW): **UNILEVER N.V.** [NL/NL]; Weena 455, 3013 AL Rotterdam (NL).

(71) **Applicant** (for AE, AG, AU, BB, BH, BN, BW, BZ, CA, CY, EG, GB, GD, GH, GM, IE, IL, IN, KE, KN, KW, LC, LK, LS, MT, MW, MY, NA, NG, NZ, OM, PG, QA, RW, SA, SC, SD, SG, SL, SZ, TT, TZ, UG, VC, ZA, ZM, ZW only): **UNILEVER PLC** [GB/GB]; Unilever House, 100 Victoria Embankment, London Greater London EC4Y 0DY (GB).

(71) **Applicant** (for US only): **CONOPCO, INC., D/B/A UNILEVER** [US/US]; 800 Sylvan Avenue AG West, S. Wing, Englewood Cliffs, New Jersey 07632 (US).

(72) **Inventors**: **BARBUZZI, Elena, Maria, Gabriella**; Unilever Italy Holdings Srl Via Lever Gibbs, 3, 26841 Casalpusterlengo (IT). **VAN DEURZEN, Maria, Petra, J**; Unilever R&D Vlaardingen B.V. Olivier van Noortlaan 120, 3133 AT Vlaardingen (NL). **GEERSE, Kees, Bert**; Unilever R&D Vlaardingen B.V. Olivier van Noortlaan 120, 3133 AT Vlaardingen (NL). **MOLL, Robert, Jan**; Unilever R&D Vlaardingen B.V. Olivier van Noortlaan

120, 3133 AT Vlaardingen (NL). **TARENTINI, Ferdinando**; Unilever Italy Holdings Srl Via Lever Gibbs, 3, 26841 Casalpusterlengo (IT).

(74) **Agent**: **BOERMA, Caroline**; Unilever Patent Group, Olivier van Noortlaan 120, 3133 AT Vlaardingen (NL).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report (Art. 21(3))

(54) **Title**: POURABLE DETERGENT SUSPENSION COMPRISING A DYED FLUID PHASE AND SUSPENDED PARTICLES

(57) **Abstract**: The invention relates to pourable detergent suspension comprising 85-99.2 wt.% of a dyed fluid phase and 0.8-15 wt.% of suspended, particles having a diameter in the range of 0.1-2 mm, said suspension comprising: • 35-75 wt.% of liquid component selected from water, glycerol and mixtures thereof, said liquid component comprising 8-25% water and at least 20% glycerol, by weight of the detergent suspension; • 8-50 wt.% of one or more aminocarboxylate chelants; • 0.01-1 wt.% of one or more dye substances; wherein the combination of the liquid component and the one or more aminocarboxylate chelants represents at least 60 wt.% of the detergent suspension; wherein the suspension has a water activity at 20°C of not more than 0.7; and wherein the dyed fluid phase has a reflective color represented by a chromaticity (a*), chromaticity (b*) and a lightness (L*) expressed by the CIE Lab color coordinate system meeting the following conditions: (a* + b*) ≤ 20; 20 ≤ L* ≤ 60; and at least one of the following conditions: b* ≤ 0; -40 ≤ a* ≤ 50; (a* + b*) ≤ 0; 25 ≤ L* ≤ 50. The pourable detergent composition combines a very attractive appearance with high stability, and is easy to manufacture.



POURABLE DETERGENT SUSPENSION COMPRISING A DYED FLUID PHASE AND SUSPENDED PARTICLES

5 TECHNICAL FIELD OF THE INVENTION

The present invention relates to a pourable detergent suspension comprising 85-99.2 wt.% of a dyed fluid phase and 0.8-15 wt.% of suspended, particles having a diameter in the range of 0.1-2 mm, said detergent suspension comprising:

- 10 • 35-75 wt.% of liquid component selected from water, glycerol and mixtures thereof, said liquid component comprising 8-25% water and at least 20% glycerol, by weight of the detergent suspension;
- 8-50 wt.% of one or more aminocarboxylate chelants;
- 0.01-1 wt.% of one or more dye substances;
- 15 wherein the combination of the liquid component and the one or more aminocarboxylate chelants represents at least 60 wt.% of the detergent suspension; wherein the suspension has a water activity of not more than 0.7; and wherein the dyed fluid phase has a reflective color represented by a chromaticity (a^*), chromaticity (b^*) and a lightness (L^*) expressed by the CIE *Lab* color coordinate system meeting the following conditions:
- 20 $(a^* + b^*) \leq 20$;
 $20 \leq L^* \leq 60$; and at least one of the following conditions:
 $b^* \leq 0$;
 $-40 \leq a^* \leq 50$;
 $(a^* + b^*) \leq 0$;
- 25 $25 \leq L^* \leq 50$.

The detergent suspension of the present invention combines a very attractive appearance with high stability and is easy to manufacture.

30

BACKGROUND OF THE INVENTION

Detergent formulations typically contain a number of different active components, including surfactants, builders, enzymes and bleaching agents.

35

Surfactants are employed to release stains and soil and to disperse the released components into the cleaning liquid. Enzymes help to remove stubborn stains of proteins, starch and lipids by hydrolyzing these components. Bleaching agents are employed in detergent compositions to remove bleachable stains, such as those associated with tea, coffee, red wine, and various fruit and vegetable products, by oxidizing the components that make up these stains. Typical bleaching agents for use in detergent formulations are chlorine- and peroxygen-based compounds, such as hypochlorite and percarbonate bleach, respectively.

Builders are incorporated in detergent formulations to complex magnesium and calcium ions as well as to maintain alkaline pH conditions. Phosphorous based builders, such as phosphates, have been used for many years in a wide variety of detergent compositions. However, as part of an increasing trend towards environmentally friendly detergent compositions, alternative building agents have been developed and these alternative builders have found their way into commercial detergent products. The aminocarboxylate chelant L-glutamic-N,N-diacetate is an example of an environmentally friendly builder that is used in commercial detergent products. Generally, aminocarboxylate chelants are present in detergent formulations in the form of their (fully deprotonated) sodium salts. Aqueous solutions of aminocarboxylate salts are alkaline.

Liquid detergent formulations have been developed as these products offer the advantage over powdered formulations that they are easy to dose, may contain higher concentrations of active ingredients, suffer less from moisture spoilage during storage and/or are more easily dispersed into aqueous cleaning liquid. In order to provide liquid detergent compositions that deliver cleaning, spotting and filming performance similar to that of a powdered formulation it is necessary to include components that remain undissolved in the liquid product matrix. These undissolved components need to be homogeneously suspended throughout the product to guarantee a constant, optimum cleaning result. Although this may be achieved by instructing the user to shake the product before use, it is clearly preferable to provide the liquid detergent formulation in the form of a suspension that remains stable during the lifecycle of the product. This objective, however, is very difficult to achieve as suspensions demix over time because suspended particles are subject to sedimentation and creaming/floating phenomena.

Bleaching agents and enzymes are moisture-sensitive detergent ingredients that lose their activity over time if the water activity of a detergent composition is too high.

EP-A 1 129 160 describes liquid aqueous cleaning compositions containing water, glycerol, builder, enzyme and thickener.

- 5 WO 2013/092276 describes detergent formulations containing GLDA, water, citric acid, nonionic surfactant, coated spray-dried percarbonate, enzymes and other ingredients.

WO 2014/107578 describes detergent compositions containing water, glycerol, polyaminocarboxylic acid (chelating agent), nonionic surfactant, enzymes.

10

EP-A 1 129 160 describes liquid aqueous cleaning compositions containing water, glycerol, builder, enzyme and thickener.

- US 2010/0081600 describes a liquid detergent composition exhibiting an at least two color effects, said composition comprising:

15

a) a cleaning system;

b) an aesthetic system comprising:

- i. a colored interference pigment having a color and showing an absorbance minimum in the range from about 380 to about 750 nm range of the light spectrum, and

20

- ii. a dye system,

wherein the color of the colored interference pigment is selected so as to be complementary to a color reflected by the composition comprising the dye in absence of the colored interference pigment.

- 25 DE-A 10 2014 212643 relates to liquid ADW detergent compositions comprising a liquid and a solid enzyme formulation. Example 1 describes a liquid ADW detergent containing glycerol, water, dye and solid enzyme.

WO 2015/181570 relates to an aqueous gel or liquid detergent composition, comprising:

30

- 5 to 60 wt% of an aminocarboxylate builder;
- a dye; and
- polyalkyleneimine.

35 **SUMMARY OF THE INVENTION**

The inventors have developed a pourable detergent composition that combines a very attractive appearance with high stability, and which is easy to manufacture.

- 5 The pourable detergent composition of the present invention comprises a blue or green coloured fluid phase and light specks of particles that are suspended in the coloured fluid phase. The combination of the liquid component and the aminocarboxylate chelant forms a homogeneous fluid that contains the dye and that at the same time is capable of keeping the particles in suspension.

10

The inventors have found that in order to obtain a stable suspension it is important to balance the relative concentrations of the ingredients, especially those of water, glycerol and aminocarboxylate chelants, so as to achieve a water activity that does not exceed 0.75. Both glycerol and aminocarboxylate chelants are hygroscopic ingredients that are capable of

- 15 reducing the water activity of water containing compositions.

The pourable detergent suspension of the present invention comprises 85-99.2 wt.% of a dyed fluid phase and 0.8-15 wt.% of suspended, particles having a diameter in the range of 0.1-2 mm, said suspension comprising:

- 20 • 35-75 wt.% of liquid component selected from water, glycerol and mixtures thereof, said liquid component comprising 8-25% water and at least 20% glycerol, by weight of the detergent suspension;
- 8-50 wt.% of one or more aminocarboxylate chelants;
 - 0.01-1 wt.% of one or more dye substances;

- 25 wherein the combination of the liquid component and the one or more aminocarboxylate chelants represents at least 60 wt.% of the detergent suspension; wherein the suspension has a water activity at 20°C of not more than 0.7; and wherein the dyed fluid phase has a reflective color represented by a chromaticity (a^*), chromaticity (b^*) and a lightness (L^*) expressed by the CIE *Lab* color coordinate system meeting the following conditions:

- 30 $(a^* + b^*) \leq 20$;

$20 \leq L^* \leq 60$; and at least one of the following conditions:

$b^* \leq 0$;

$-40 \leq a^* \leq 50$;

$(a^* + b^*) \leq 0$;

- 35 $25 \leq L^* \leq 50$.

Although the inventors do not wish to be bound by theory it is believed that whereas the presence of a substantial amount of liquid component is essential for rendering the suspension pourable, the aminocarboxylate chelant renders the suspension sufficiently

viscous to keep the particles in suspension. In addition, the combination of aminocarboxylate chelant and glycerol ensures that even if the suspension contains a significant quantity of water activity can be reduced to 0.75 or less. A low water activity is important, for instance, in case the particles contain moisture sensitive ingredients, such as bleaching agent or enzymes.

The invention also provides a packaged detergent product comprising a container and a suspension as described herein below, said container comprising a container wall and an outlet, and said suspension being contained inside the container, wherein at least a part of the container wall is translucent or transparent. The invention also allows to provide for the suspension being packaged in a single dose unit such as a sachet (pouch) or capsule.

DETAILED DESCRIPTION OF THE INVENTION

A first aspect of the invention relates to a pourable detergent suspension comprising 85-99.2 wt.% of a dyed fluid phase and 0.8-15 wt.% of suspended, particles having a diameter in the range of 0.1-2 mm, said suspension comprising:

- 35-75 wt.% of liquid component selected from water, glycerol and mixtures thereof, said liquid component comprising 8-25% water and at least 20% glycerol, by weight of the detergent suspension;
- 8-50 wt.% of one or more aminocarboxylate chelants;
- 1-30 wt.% of one or more surfactants;
- 0.01-1 wt.% of one or more dye substances;

wherein the combination of the liquid component and the one or more aminocarboxylate

chelants represents at least 60 wt.% of the detergent suspension; wherein the suspension has a water activity at 20°C of not more than 0.7; and wherein the dyed fluid phase has a reflective color represented by a chromaticity (a^*), chromaticity (b^*) and a lightness (L^*) expressed by the CIE *Lab* color coordinate system meeting the following conditions:

$$(a^* + b^*) \leq 20;$$

$$20 \leq L^* \leq 60; \text{ and at least one of the following conditions:}$$

$$\begin{aligned}b^* &\leq 0; \\ -40 &\leq a^* \leq 50; \\ (a^* + b^*) &\leq 0; \\ 25 &\leq L^* \leq 50.\end{aligned}$$

5

The term "pourable" as used herein refers to a composition that is able to flow under ambient conditions. Thixotropic compositions that can be rendered pourable by shear thinning are also regarded as pourable.

- 10 The term "particles" as used herein, unless indicated otherwise, refers to a particulate matter in liquid or solid form, preferably solid form.

The term "aminocarboxylate chelant" as used herein refers to compounds containing one or more nitrogen atoms connected through carbon atoms to one or more carboxyl groups, which
15 form strong complexes with metal ions by donation of electron pairs from the nitrogen and oxygen atoms to the metal ion to form multiple chelate rings.

- The term "thixotropic" as used herein refers to compositions (e.g. gels or fluids) that are viscous under quiescent conditions and that become less viscous when shaken, agitated, or
20 otherwise stressed. In thixotropic compositions, this so called "shear thinning effect" is reversible, i.e. the composition will return to a more viscous state once it is no longer subjected to shear stress.

- A *Lab* color space is a color-opponent space with dimension *L* for lightness and *a* and *b* for
25 the color-opponent dimensions, based on nonlinearly compressed (e.g. CIE XYZ color space) coordinates. The $L^*a^*b^*$ color space includes all perceivable colors. One of the most important attributes of the $L^*a^*b^*$ -model is device independence. This means that the colors are defined independent of their nature of creation or the device they are displayed on. The lightness, L^* , represents the darkest black at $L^* = 0$, and the brightest white at $L^* = 100$. The
30 color channels, a^* and b^* , will represent true neutral gray values at $a^* = 0$ and $b^* = 0$. The red/green opponent colors are represented along the a^* axis, with green at negative a^* values and red at positive a^* values. The yellow/blue opponent colors are represented along the b^* axis, with blue at negative b^* values and yellow at positive b^* values. The scaling and limits of the a^* and b^* axes runs in the range of -100 to 100.

35

Whenever reference is made herein to water content, unless indicated otherwise, said water content includes unbound (free) as well as bound water.

Whenever a parameter, such as a concentration or a ratio, is said to be less than a certain upper limit it should be understood that in the absence of a specified lower limit the lower limit for said parameter is 0.

Whenever an amount or concentration of a component is quantified herein, unless indicated otherwise, the quantified amount or quantified concentration relates to said component *per se*, even though it may be common practice to add such a component in the form of a solution or of a blend with one or more other ingredients.

The detergent suspension of the present invention preferably comprises 87-98.5 wt.% of a dyed fluid phase and 1.5-13 wt.% of suspended, particles having a diameter in the range of 0.1-2 mm. Most preferably, the detergent suspension comprises 90-98 wt.% of a dyed fluid phase and 2-12 wt.% of suspended, particles having a diameter in the range of 0.1-2 mm.

The combination of glycerol, water and the one or more aminocarboxylate chelants typically represent at least 63 wt.%, preferably at least 65 wt.% of the detergent suspension.

The detergent suspension typically has a water activity of 0.2 to 0.6 at 20°C. More preferably, the water activity of the detergent suspension at 20°C is in the range of 0.3 to 0.5, most preferably of 0.35 to 0.45.

25 *Fluid phase*

The fluid phase of the detergent suspension of the present invention largely consists of glycerol, water and aminocarboxylate chelant. The fluid phase may additionally contain liquid and non-liquid components in dissolved or non-dissolved form. Only dissolved components and non-dissolved components that are present as particles/droplets having a diameter of less than 100 µm are considered as part of the fluid phase.

Typically, the combination of the liquid component and the one or more aminocarboxylate chelants represents at least 63 wt.%, more preferably at least 65 wt.% and most preferably at least 67-95 wt.% of the detergent suspension.

The detergent suspension of the present invention preferably contains water and the one or more aminocarboxylate chelants in a weight ratio of not more than 2:1, preferably of not more than 1.5:1, most preferably of not more than 1.2:1. Water and the one or more aminocarboxylate chelants are typically contained in the detergent suspension in a weight ratio of at least 1:3, more preferably of at least 1:2 and most preferably of at least 1:1.8.

The one or more dye substances are preferably contained in the detergent suspension in a concentration of 0.02-0.5 wt.%, more preferably of 0.03-0.3 wt.%.

The one or more dye substances employed in the detergent suspension preferably are water-soluble dye substances.

The one or more dye substances that are contained in the fluid phase of the detergent suspension are preferably at least partly present in the fluid phase in dissolved form. More preferably, at least 50 wt.% of the one or more dye substances is dissolved in the fluid phase at 20°C.

The fluid phase can suitably contain other detergent ingredients besides the liquid component, aminocarboxylate chelant and the one or more dye substances. Examples of such ingredients include surfactants, anti-scaling agents, glass corrosion inhibitors, anti-tarnishing agents, perfumes and combinations thereof.

Particles

According to a particularly preferred embodiment, the detergent suspension contains at least 0.5 wt.%, more preferably at least 0.8 wt.% and most preferably at least 1.5 wt.% of particles having a diameter of 0.2-1.5 mm.

Unlike the fluid phase, the particles preferably do not contain added dye substances. Accordingly, the particles preferably contain less than 0.01 wt.%, more preferably less than 0.001 wt.% of dye substances.

The particles in the detergent suspension preferably contain at least 50 wt.% of solid component selected from bleaching agents, bleach activators, water-soluble salts, carbohydrates, enzymes and combinations thereof.

According to a particularly preferred embodiment, the particles are white or off-white.

Liquid component

The detergent suspension preferably contains 40-70 wt.%, more preferably 43-67 wt.% and
5 most preferably 45-65 wt.% of the liquid component.

Glycerol and water are preferably contained in the pourable detergent suspension in a weight ratio that lies within the range of 2:3 to 1:6, more preferably within the range of 1:2 to 1:5, most preferably within the range of 1:2.2 to 1:4.

10

The pourable detergent suspension preferably contains up to 75 wt.%, more preferably 30-60 wt.% and most preferably 32-50 wt.% glycerol.

The water content of the detergent suspension preferably is in the range of 10-22 wt.% and
15 most preferably in the range of 12-20 wt.%.

Aminocarboxylate chelant

The pourable detergent suspension preferably contains at least 10 wt.%, more preferably 12-35 wt.% and most preferably 13-30 wt.% of the one or more aminocarboxylate chelants.

20

Preferably the one or more aminocarboxylate chelants are selected from glutamic acid N,N-diacetic acid (GLDA), methylglycinediacetic acid (MGDA), iminodisuccinic acid (IDS), ethylenediaminetetraacetic acid (EDTA), diethylenetriaminepentaacetic acid (DTPA), hydroxyethyliminodiacetic acid (HEIDA), Nitrilotriacetic acid (NTA), aspartic acid
25 diethoxysuccinic acid (AES), aspartic acid-N, -diacetic acid (ASDA), hydroxyethylenediaminetetraacetic acid (HEDTA), hydroxyethylethylenediaminetriacetic acid (HEEDTA), iminodifumaric (IDF), iminoditartaric acid (IDT), iminodimaleic acid (IDMAL), iminodimalic acid (IDM), ethylenediaminedifumaric acid (EDDF), ethylenediaminedimalic acid (EDDM), ethylenediamineditartaric acid (EDDT), ethylenediaminedisuccinic acid (EDDS),
30 ethylenediaminedimaleic acid and (EDDMAL), dipicolinic acid, and their salts.

More preferably, the one or more aminocarboxylate chelants are selected from GLDA, MGDA, IDS, HEIDA, EDDS and NTA, and their salts. In an even more preferred embodiment, the one or more aminocarboxylate chelants are selected from GLDA, MGDA, IDS and their

salts. Most preferably, the the one or more aminocarboxylate chelants are selected from GLDA and salts thereof.

The GLDA employed in the present suspension preferably is an alkali metal salt of glutamic-N,N-diacetic acid. More preferably, the GLDA employed is a sodium salt of glutamic-N,N-diacetic acid. Most preferably, the GLDA employed is a tetra sodium salt of glutamic-N,N-diacetic acid.

Surfactants

- 10 The present detergent suspension preferably contains 0.5-30 wt.% of one or more surfactants. Surfactants, within the invention, are components within the classification as described in "Surfactant Science Series", Vol.82, Handbook of detergents, part A: Properties, chapter 2 (Surfactants, classification), G. Broze (ed.). Typically, the detergent composition contains 0.5-30 wt.%, preferably 1-20 wt.%, more preferably 1.3-10 wt.% of one or more
- 15 surfactants. In a preferred embodiment, the surfactants are selected from one or more non-ionic surfactants.

- According to a particularly preferred embodiment, the composition contains 0.1-15 wt.%, more preferably 0.5-10 wt.% and most preferably 1-5 wt.% of a nonionic surfactant or a
- 20 mixture of two or more non-ionic surfactants. Examples of nonionic surfactants that may be employed in the present composition include the condensation products of hydrophobic alkyl, alkenyl, or alkyl aromatic compounds bearing functional groups having free reactive hydrogen available for condensation with hydrophilic alkylene oxide, such as ethylene oxide, propylene oxide, butylene oxide, polyethylene oxide or polyethylene glycol to form nonionic surfactants.
- 25 Examples of such functional groups include hydroxy, carboxy, mercapto, amino or amido groups.

- Examples of useful hydrophobes of commercial nonionic surfactants include C8-C18 alkyl fatty alcohols, C8-C14 alkyl phenols, C8-C18 alkyl fatty acids, C8-C18 alkyl mercaptans, C8-
- 30 C18 alkyl fatty amines, C8-C18 alkyl amides and C8-C18 alkyl fatty alkanolamides.

- Accordingly, suitable ethoxylated fatty alcohols may be chosen from ethoxylated cetyl alcohol, ethoxylated ketostearyl alcohol, ethoxylated isotridecyl alcohol, ethoxylated lauric alcohol, ethoxylated oleyl alcohol and mixtures thereof. Examples of suitable nonionic surfactants for use in the invention are found in the low- to non-foaming ethoxylated/ propoxylated straight-
- 35 chain alcohols of the Plurafac™ LF series, supplied by the BASF and the Synperonic™ NCA

series supplied by Croda. Also of interest are the end-capped ethoxylated alcohols available as the SLF 18 series from BASF and the alkylpolyethylene glycol ethers made from a linear, saturated C16-C18 fatty alcohol of the Lutensol™ AT series, supplied by BASF. Other suitable nonionics to apply in the composition of the invention are modified fatty alcohol

5 polyglycolethers available as Dehypon™ 3697 GRA or Dehypon™ Wet from BASF/Cognis. Also suitable for use herein are nonionics from the Lutensol™ TO series of BASF, which are alkylpolyethylene glycol ethers made from a saturated iso-C13 alcohol. Amineoxide surfactants may also be used in the present invention as anti- redeposition surfactant.

Examples of suitable amineoxide surfactants are C10-C15 alkyl dimethylamine oxide and
10 C10-C15 acylamido alkyl dimethylamine oxide. The inventors have found that, a detergent composition that is not only chemically but also physically very stable can be produced if the nonionic surfactant employed is solid at ambient temperature. Thus, advantageously, the present composition contains 0.1 -30 wt.%, more preferably 0.5-20 wt.%, further preferred 1-10 wt.%, and most preferably 1 -5 wt.% of nonionic surfactant that is solid at 25°C.

15

If an anionic surfactant is used, the total amount present preferably is less than 5 wt.%, and more preferably not more than 2 wt.%. Furthermore, if an anionic surfactant is present, it is preferred that an antifoam agent to suppress foaming is present. Examples of suitable anionic surfactants are methylester sulphonates or sodium lauryl sulphate. It is preferred that no

20 anionic surfactant is present in the composition of the current invention.

Structuring biopolymer

In accordance with a particularly advantageous embodiment, the detergent suspension of the present invention contains a structuring biopolymer. The inventors have found that the use of
25 biopolymer that is capable of structuring water (e.g. through gelation) makes it possible to prepare a fluid product with excellent rheological properties.

Preferably, the pourable product contains at least 0.1% of structuring biopolymer by weight of water. Even more preferably, the product contains 0.2-3%, most preferably 0.3-2% of
30 structuring biopolymer by weight of water. Examples of structuring biopolymers that can be employed include xanthan gum, locust bean gum, guar gum, gum Arabic, gellan gum, carrageenan, carboxymethyl cellulose, microcrystalline cellulose, microfibrinous cellulose and combinations thereof. More preferably, the structuring biopolymer is selected from xanthan gum, guar gum, carboxymethyl cellulose, microfibrinous cellulose and combinations thereof.
35 Most preferably, the structuring biopolymer is xanthan gum.

Builders

In addition to the one or more aminocarboxylate chelants, the pourable detergent suspension may contain additional water-softening builders. Traditionally phosphorous based builders, such as phosphates have been used as builders, but due to environmental pressures other builders are preferred. These include organic builders such as citrate and inorganic builders such as carbonates, in particular sodium carbonate.

Citrate is preferably contained in the pourable detergent suspension in a concentration of 0.1-4 wt.%, more preferably of 0.2-2 wt.%, most preferably of 0.25-1.2 wt.% citric acid equivalent.

According to a particularly preferred embodiment, the detergent suspension contains 3-30 wt.%, more preferably 5-25 wt.%, most preferably 7-20 wt.% of sodium carbonate.

15 *Silicates*

Silicates may be added to the formulation. Silicates can act as builder, buffering agent or article care agent. Preferred silicates are sodium silicate such as sodium disilicate, sodium metasilicate and crystalline phyllosilicates and mixtures thereof. Silicates are preferably used in the detergent suspension in a concentration of 0.5 to 8%, more preferably of 0.8 to 6% by weight of the suspension.

Enzymes

Examples of enzymes suitable for use in the detergent suspension of this invention include lipases, cellulases, peroxidases, proteases (proteolytic enzymes), amylases (amylolytic enzymes) and others which degrade, alter or facilitate the degradation or alteration of biochemical soils and stains encountered in cleansing situations so as to remove more easily the soil or stain from the object being washed to make the soil or stain more removable in a subsequent cleansing step. Both degradation and alteration can improve soil removal.

30 Preferably, the one or more active enzymes contained in the present suspension are selected from protease, amylase, cellulase, peroxidase, mannanase, pectate lyase and lipase. Most preferably, the active enzyme is selected from protease, amylase and combinations thereof.

The suspension of the present invention typically contains at least 10 mg/kg, more preferably at least 20 mg/kg, even more preferably at least 50 mg/kg and most preferably at least 100

mg/kg of active enzyme. The concentration of active enzyme preferably does not exceed 50 g/kg, more preferably it does not exceed 40 g/kg and most preferably it does not exceed 30 g/kg.

- 5 According to a particularly preferred embodiment, the suspension contains at least 10 mg/kg, more preferably at least 20 mg/kg and most preferably at least 50 mg/kg of active amylase.

According to another especially preferred embodiment, the suspension contains at least 100 mg/kg, more preferably at least 200 mg/kg and most preferably at least 400 mg/kg of active
10 protease.

Enzymes may be added in liquid or in encapsulated form. Examples of encapsulated enzymes are enzyme granule types D, E and HS by Genencor and granule types , T, GT, TXT and Eivity™ of Novozymes.

15

The proteolytic enzymes in this invention include metal loproteases and serine proteases, including neutral or alkaline microbial serine protease, such as subtilisins (EC 3.4.21 .62). The proteolytic enzymes for use in the present invention can be those derived from bacteria of fungi. Chemically or genetically modified mutants (variants) are included. Preferred
20 proteolytic enzymes are those derived from

Bacillus, such as B. lentus, B. gibsonii, B. subtilis, B. licheniformis, B. alkalophilus, B. amyloliquefaciens and Bacillus pumilus, of which B. lentus and B. gibsonii are most preferred. Examples of such proteolytic enzymes are Excellase™, Properase™, Purafect™, Purafect™
25 Prime, Purafect™ Ox by Genencor; and those sold under the trade names Blaze™, Ovozyme™, Savinase™, Alcalase™, Everlase™, Esperase™, Relase™, Polarzyme™, Liquinase™ and Coronase™ by Novozymes.

The amylolytic enzymes for use in the present invention can be those derived from bacteria or
30 fungi. Chemically or genetically modified mutants (variants) are included. Preferred amylolytic enzyme is an alpha-amylase derived from a strain of Bacillus, such as B. subtilis, B. licheniformis, B. amyloliquefaciens or B. stearothermophilus. Examples of such amylolytic enzymes are produced and distributed under the trade name of Stainzyme™, Stainzyme™ Plus, Termamyl™, Natalase™ and Duramyl™ by Novozymes; as well as Powerase™,

Purastar™, Purastar™ Oxam by Genencor. Stainzyme™, Stainzyme™ Plus and Powerase™ are the preferred amylases.

In accordance with a particularly preferred embodiment of the invention, the suspension
5 contains active protease and the protease activity of the freshly prepared suspension decreases by not more than 70%, more preferably by not more than 50% and most preferably by not more than 20% when the suspension is stored in a closed container for 8 weeks at 20 °C. Well known enzyme stabilizers such as polyalcohols/borax, calcium, formate or protease inhibitors like 4-formylphenyl boronic acid may also be present in the suspension.

10

Bleach

The present detergent suspension preferably contains at least 0.3 wt.%, more preferably 1-15 wt.% and most preferably 2-12 wt.% of bleaching agent.

15 The bleaching agent may suitably comprise a chlorine-, or bromine-releasing agent or a peroxygen compound. Preferably, the bleaching agent is selected from peroxides (including peroxide salts such as sodium percarbonate), organic peracids, salts of organic peracids and combinations thereof. More preferably, the bleaching agent is a peroxide. Most preferably, the bleaching agent is a percarbonate.

20

Examples of peroxides are acids and corresponding salts of monopersulphate, perborate monohydrate, perborate tetrahydrate, and percarbonate. Organic peracids useful herein include alkyl peroxy acids and aryl peroxyacids such as peroxybenzoic acid and ring substituted peroxybenzoic acids (e.g. peroxy- α - naphthoic acid), aliphatic and substituted
25 aliphatic monoperoxy acids (e.g. peroxy lauric acid and peroxy stearic acid), and phthaloyl amido peroxy caproic acid (PAP).

Typical diperoxy acids useful herein include alkyl diperoxy acids and aryldiperoxy acids, such as 1,12 di-peroxy-dodecanedioic acid (DPDA), 1,9 diperoxyazelaic acid, diperoxybrassylic
30 acid, diperoxysebacic acid and diperoxy-isophthalic acid, and 2 decyldiperoxybutane 1,4 dioic acid.

The detergent suspension of the present invention preferably contains bleaching agent in the form of particles. More preferably, the suspension contains 0.3-15 wt.%, more preferably 0.5-
35 10 wt.% of particles of bleaching agent.

According to a preferred embodiment, the particles of bleaching agent are coated particles comprising one or more core particles that contain the bleaching agent, which one or more core particles are enclosed by a water-soluble coating. The water-soluble coating

- 5 advantageously comprises a coating agent selected from alkali sulphate, alkali carbonate or alkali chloride and combinations thereof.

The detergent suspension may contain one or more bleach activators such as peroxyacid bleach precursors. Peroxyacid bleach precursors are well known in the art. As non-limiting
10 examples can be named N,N,N',N'-tetraacetyl ethylene diamine (TAED), sodium nonanoyloxybenzene sulphonate (SNOBS), sodium benzyloxybenzene sulphonate (SBOBS) and the cationic peroxyacid precursor (SPCC) as described in US-A-4,751 ,015.

- If desirable, a bleach catalyst, such as the manganese complex, e.g. Mn-Me TACN, as
15 described in EP-A-0458397, or the sulphonimines of US-A-5,041 ,232 and US-A- 5,047,163, can be incorporated. Cobalt or iron catalysts can also be used.

Dispersing polymers

- The detergent suspension may suitably contain one or more dispersing polymers. Dispersing
20 polymers as referred to in this invention are chosen from the group of anti-spotting agents and/or anti-scaling agents.

Examples of suitable anti-spotting polymeric agents include hydrophobically modified polycarboxylic acids such as Acusol™ 460 ND (ex Dow) and Alcosperse™ 747 by

- 25 AkzoNobel, whereas also synthetic clays, and preferably those synthetic clays which have a high surface area are very useful to prevent spots, in particular those formed where soil and dispersed remnants are present at places where the water collects on the glass and spots formed when the water subsequently evaporates.

- 30 Examples of suitable anti-scaling agents include organic phosphonates, amino carboxylates, polyfunctionally-substituted compounds, and mixtures thereof.

Particularly preferred anti-scaling agents are organic phosphonates such as alpha-hydroxy-2 phenyl ethyl diphosphonate, ethylene diphosphonate, hydroxy 1 ,1 - hexylidene, vinylidene 1

- 35 ,1 -diphosphonate, 1 ,2-dihydroxyethane 1 ,1 -diphosphonate and hydroxy-ethylene 1 ,1 -

diphosphonate. Most preferred is hydroxy-ethylene 1,1 - diphosphonate (EDHP) and 2-phosphono-butane, 1,2,4-tricarboxylic acid (Bayhibit ex Bayer). Suitable anti-scaling agents are water soluble dispersing polymers prepared from an allyloxybenzenesulfonic acid monomer, a methallyl sulfonic acid monomer, a copolymerizable nonionic monomer and a
5 copolymerizable olefinically unsaturated carboxylic acid monomer as described in US 5 547 612 or known as acrylic sulphonated polymers as described in EP 851 022. Polymers of this type include polyacrylate with methyl methacrylate, sodium methallyl sulphonate and sulphophenol methallyl ether such as Alcosperse™ 240 supplied (AkzoNobel). Also suitable is a terpolymer containing polyacrylate with 2-acrylamido-2 methylpropane sulphonic acid
10 such as Acumer 3100 supplied by Dow. As an alternative, polymers and co-polymers of acrylic acid having a molecular weight between 500 and 20,000 can also be used, such as homo-polymeric polycarboxylic acid compounds with acrylic acid as the monomeric unit. The average weight of such homo-polymers in the acid form preferably ranges from 1,000 to 100,000 particularly from 3,000 to 10,000 e.g. Sokalan™ PA 25 from BASF or Acusol™ 425
15 from Dow.

Also suitable are polycarboxylates co-polymers derived from monomers of acrylic acid and maleic acid, such as CP 5 from BASF. The average molecular weight of these polymers in the acid form preferably ranges from 4,000 to 70,000. Modified polycarboxylates like
20 Sokalan™ CP42, Sokalan™ CP50 from BASF or Alcoguard™ 4160 from AkzoNobel may also be used.

Mixture of anti-scaling agents may also be used. Particularly useful is a mixture of organic phosphonates and polymers of acrylic acid. It is preferable if the level of dispersing polymers
25 ranges from 0.2 to 10 wt.% of the total suspension, preferably from 0.5 to 8 wt.%, and further preferred from 1 to 6 wt.%.

Other ingredients Glass corrosion inhibitors can prevent the irreversible corrosion and iridescence of glass surfaces in machine dishwasher detergents. The detergent suspension
30 may suitably contain glass corrosion inhibitors. Suitable glass corrosion agents can be selected from the group the group consisting of salts of zinc, bismuth, aluminum, tin, magnesium, calcium, strontium, titanium, zirconium, manganese, lanthanum, mixtures thereof and precursors thereof. Most preferred are salts of bismuth, magnesium or zinc or combinations thereof. Preferred levels of glass corrosion inhibitors in the present suspension
35 are 0.01-2 wt.%, more preferably 0.1 - 0.5 wt.%.

Anti-tarnishing agents may prevent or reduce the tarnishing, corrosion or oxidation of metals such as silver, copper, aluminium and stainless steel. Anti-tarnishing agents such as benzotriazole or bis-benzotriazole and substituted or substituted derivatives thereof and those described in EP 723 577 (Unilever) may also be included in the suspension. Other anti-tarnishing agents that may be included in the detergent suspension are mentioned in WO 94/26860 and WO 94/26859. Suitable redox active agents are for example complexes chosen from the group of cerium, cobalt, hafnium, gallium, manganese, titanium, vanadium, zinc or zirconium, in which the metal are in the oxidation state of II, III, IV, V or VI.

Optionally other components may be added to the formulation such as perfume, colorant or preservatives. The desired viscosity profile of the detergent suspension depends on the end use of the product. It may be a liquid, gel or a paste depending on the application.

Rheology

According to a particularly preferred embodiment of the present invention the detergent suspension is a thixotropic composition.

The term "thixotropic" means that the product is viscous under quiescent conditions and become less viscous when shaken, agitated, or otherwise stressed. In thixotropic compositions, this so called "shear thinning effect" is reversible, i.e. the composition will return to a more viscous state once it is no longer subjected to shear stress. This thixotropic behavior of the detergent suspension can be demonstrated by measuring the storage modulus (G') and the loss modulus (G'') of the product as a function of angular frequency (ω) on a rheometer in oscillatory mode. Both G' and G'' of the pourable product increase as a function of angular frequency (ω), be it that G'' increases at a faster rate than G' . At very low angular frequency (ω) G'' of the pourable product is lower than G' , but at an ω in the range of 0.05-50 rad/s G'' surpasses G' .

Both the storage modulus (G') and the loss modulus (G'') of the pourable product are determined at 20°C using Anton Paar® MCR 302 rheometer, using plate-plate geometry, spindle PP50/S (sandblasted) and a gap size of 3mm. The program settings applied are as follows:

- A Strain γ is chosen in the Linear Visco-elastic range of the product (LVER is determined by an Amplitude Sweep). The strain is kept constant on 0.1%.

- An increasing ramp log of angular frequency ω is set on the sample from low to high frequency, starting at 0.01 rad/s. The end ω is 100 rad/s unless the sample is very stiff.
 - The setting in which the measuring points are gathered is the 'no time settings'. In this modus the apparatus waits for a steady state situation before it takes his measuring point.
- 5 • Every decade six measuring points are taken.

Using oscillatory rheology, it is possible to quantify both the viscous-like and the elastic-like properties of a material at different time scales. The basic principle of an oscillatory rheometer is to induce a sinusoidal shear deformation in the sample and measure the resultant stress response; the time scale probed is determined by the frequency of oscillation, ω , of the shear deformation. A sample is placed between two plates. While the top plate remains stationary, a motor rotates the bottom plate, thereby imposing a time dependent strain $\gamma(t) = \gamma_0 \sin(\omega t)$ on the sample. Simultaneously, the time dependent stress $\sigma(t)$ is quantified by measuring the torque that the sample imposes on the top plate.

15

Measuring this time dependent stress response at a single frequency immediately reveals key differences between materials. If the material is an ideal elastic solid, then the sample stress is proportional to the strain deformation, and the proportionality constant is the shear modulus of the material. The stress is always exactly in phase with the applied sinusoidal strain deformation.

20

In contrast, if the material is a purely viscous fluid, the stress in the sample is proportional to the rate of strain deformation, where the proportionality constant is the viscosity of the fluid. The applied strain and the measured stress are out of phase, with a phase angle $\delta = \pi/2$.

25

Viscoelastic materials show a response that contains both in-phase and out-of-phase contributions. These contributions reveal the extents of solid-like and liquid-like behavior. As a consequence, the total stress response shows a phase shift δ with respect to the applied strain deformation that lies between that of solids and liquids, $0 < \delta < \pi/2$. The viscoelastic behaviour of the system at ω is characterised by the storage modulus, $G'(\omega)$, and the loss modulus, $G''(\omega)$, which respectively characterise the solid-like and fluid-like contributions to the measured stress response. For a sinusoidal strain deformation $\gamma(t) = \gamma_0 \sin(\omega t)$, the stress response of a viscoelastic material is given by $\sigma(t) = G'(\omega) \gamma_0 \sin(\omega t) + G''(\omega) \gamma_0 \cos(\omega t)$.

30

Whether the product behaves more solid-like or more liquid-like depends on the time scale at which it is deformed. At the lowest accessible frequencies the pourable product of the present invention has a loss modulus that is lower than the storage modulus, indicating solid-like behavior, while at the highest frequencies accessed the loss modulus dominates the response, indicating viscous-like behavior.

In accordance with a particularly advantageous embodiment of the present invention the detergent suspension is a thixotropic suspension having a storage modulus at 20°C ($G'(\omega)$) and a loss modulus at 20°C ($G''(\omega)$), both moduli measured as a function of angular frequency (ω) on a rheometer in oscillatory mode operating at a strain of 0.1%, wherein:

- $G''(\omega) > G'(\omega)$ at angular frequencies (ω) in the range of 50 to 100 rad/s, and
- $G''(\omega) < G'(\omega)$ at angular frequencies (ω) in the range of 0.01-0.05 rad/s.

Especially preferred is a detergent suspension having a storage modulus (G') and a loss modulus (G'') that meet at least one of the following conditions:

- $G''(\omega) > G'(\omega)$ at angular frequencies (ω) in the range of 30 to 100 rad/s, more preferably in the range of 10 to 100 rad/s;
- $G''(\omega) < G'(\omega)$ at angular frequencies (ω) in the range of 0.01 to 0.2 rad/s, more preferably in the range of 0.01 to 0.5 rad/s.

The pourable detergent suspension typically has a storage modulus (G') at 0.2 rad/s in the range of 1 to 100 Pa, more preferably in the range of 8 to 30 Pa, most preferably in the range of 10 to 20 Pa.

The loss modulus (G'') of the pourable detergent suspension at 0.2 rad/s preferably is in the range of 1 to 100 Pa, more preferably in the range of 3 to 60 Pa, most preferably in the range of 8 to 30 Pa.

Packaging

The pourable detergent composition is in particular suitable to be packaged in a container comprising a container wall and an outlet, such as a bottle, to allow adaptation of the detergent dosing to the amount of soil on the dish ware. Such a container or bottle is suitable for multiple use. In a preferred embodiment, the container has at least one translucent outer wall.

In another embodiment, the pourable detergent composition can be packaged in a container suitable for single use.

In accordance with this embodiment, such a single use container holds one unit of the detergent formulation and is at least partly made from water-soluble material. Examples of
5 containers that may be used in accordance with this embodiment are sachets (pouches) and capsules.

Suitably, the single use container is not only water-insoluble, but also water-permeable. More particularly, it is preferred that the container is made of a water-permeable and water-soluble
10 polymer selected from polyvinyl alcohol, cellulose ethers, polyethylene oxide, starch, polyvinylpyrrolidone, polyacrylamide, polyvinyl methyl ether-maleic anhydride, polymaleic anhydride, styrene maleic anhydride, hydroxyethylcellulose, methylcellulose, polyethylene glycols, carboxymethylcellulose, polyacrylic acid salts, alginates, acrylamide copolymers, guar gum, casein, ethylene-maleic anhydride resin series, polyethylene imine, ethyl
15 hydroxyethylcellulose, ethyl methylcellulose, hydroxyethyl methylcellulose and combinations thereof. Even more preferably, the single use container is made of polyvinyl alcohol, polyethelene oxide, polyvinylpyrrolidone and combinations thereof.

In another preferred embodiment, the single use container is made of a water-permeable and
20 water-insoluble polymer selected from butyral resin, polyvinyl acetal, poly(vinyl butyral-co-vinyl alcohol-co-vinyl acetate), polyvinyl butyrate, polyvinyl acetate and combinations and comonomers thereof.

Most preferably, the single use container is made of polyvinyl alcohol, a copolymer of
25 polyvinyl alcohol and combinations thereof. Polyvinyl alcohols preferred have a weight average molecular weight between 1,000 and 300,000, more preferably, between 2,000 and 150,000, and most preferably, between 3,000 and 100,000.

According to a preferred embodiment, the container comprises 5-40 ml, more preferably 8-30-
30 ml and most preferably 10-20-ml of the detergent formulation.

The invention is further illustrated by the following non-limiting examples.

EXAMPLES

A thixotropic machine dishwashing product was prepared on the basis of the recipe that is shown in Table 1.

5 **Table 1**

Ingredients	Wt.%
Glycerol	47.42
Citric Acid (50%)	1.43
Dissolvine™ GL 47-S ¹	9.40
Dissolvine™ PD-S 2 ²	18.40
Water	7.99
Xanthan Gum	0.21
Carbonate ash light	12.05
Percarbonate ³	1.10
Dye ⁴	0.14
Lutensol™ AT80 (nonionic surfactant)	1.87

¹ Contains appr. 48 wt.% GLDA and 45 wt.% water

² Contains appr. 85 wt.% GLDA and 9 wt.% water

³ Coated percarbonate, 98 wt.% between 0.2 mm and 1.4 mm

⁴ Liquitint Blue HP (ex Milliken)

10

The product was prepared as follows: a liquid premix was made by mixing glycerol and xanthan gum to a homogeneous suspension. Next, water was added under constant stirring. After that Dissolvine™ GL 47-S and citric acid were dosed at ambient temperature. Next, the Dissolvine™ PD-S was mixed in. Finally the remaining ingredients were added to the mix

15 under stirring. All ingredients were mixed in under vacuum to minimize formation of air bubbles.

The product so obtained was filled into a bottle made of transparent polypropylene. The detergent product was a stable suspension that did not suffer from phase separation or
 20 sedimentation when stored under ambient conditions. The product had a very attractive blue colour and showed light specks percarbonate particles suspended in blue fluid. The product was quite viscous but could be poured from the bottle without any problems.

The CIE *Lab* color values of the product were measured and are shown in Table 2.

25

Table 2

L* (0 to 100)	35
a* (-100 to 100)	4
b* (-100 to 100)	-22

Claims

1. A pourable detergent suspension comprising 85-99.2 wt.% of a dyed fluid phase and 0.8-15 wt.% of particles having a diameter in the range of 0.1-2 mm, said detergent suspension comprising:
 - 35-75 wt.% of liquid component selected from water, glycerol and mixtures thereof, said liquid component comprising 8-25% water and at least 20% glycerol, by weight of the detergent suspension;
 - 8-50 wt.% of one or more aminocarboxylate chelants;
 - 0.01-1 wt.% of one or more dye substances;wherein the combination of the liquid component and the one or more aminocarboxylate chelants represents at least 60 wt.% of the detergent suspension; wherein the suspension has a water activity at 20°C of not more than 0.7; and wherein the dyed fluid phase has a reflective color represented by a chromaticity (a^*), chromaticity (b^*) and a lightness (L^*) expressed by the CIE *Lab* color coordinate system meeting the following conditions:
 $(a^* + b^*) \leq 20$;
 $20 \leq L^* \leq 60$; and at least one of the following conditions:
 $b^* \leq 0$;
 $-40 \leq a^* \leq 50$;
 $(a^* + b^*) \leq 0$;
 $25 \leq L^* \leq 50$.
2. Suspension according to claim 1, wherein the detergent suspension comprises a blue or green coloured fluid phase.
3. Suspension according to claim 1 or 2, wherein the particles contain at least at least 50 wt.% of solid component selected from bleaching agents, bleach activators, water-soluble salts, carbohydrates, enzymes and combinations thereof.
4. Suspension according to any one of the preceding claims, wherein the suspension contains water and the one or more aminocarboxylate chelants in a weight ratio of not more than 2:1, preferably of not more than 3:2.

5. Suspension according to any one of the preceding claims, wherein the one or more aminocarboxylate chelants are selected from GLDA, MGDA, IDS and combinations thereof.
6. Suspension according to any one of the preceding claims, wherein the suspension contains water and glycerol in a weight ratio water to glycerol in the range of 2:3 to 1:6.
7. Suspension according to any one of the preceding claims, wherein the suspension contains 10-30 wt.% aminocarboxylate chelant.
8. Suspension according to any one of the preceding claims, wherein the suspension contains 0.5-30 wt.%, preferably 1-20 wt.% of one or more surfactants.
9. Suspension according to any one of the preceding claims, wherein the suspension contains at least 0.1% of gelling biopolymer by weight of water.
10. Suspension according to claim 9, wherein the gelling biopolymer is xanthan gum.
11. Suspension according to any one of the preceding claims, wherein the suspension contains citrate in a concentration of 0.1-4 wt.% citric acid equivalent.
12. Suspension according to any one of the preceding claims; said detergent suspension having a storage modulus at 20°C ($G'(\omega)$) and a loss modulus at 20°C ($G''(\omega)$), both moduli measured as a function of angular frequency (ω) on a rheometer in oscillatory mode operating at a strain of 0.1%, wherein:
 - $G''(\omega) > G'(\omega)$ at angular frequencies (ω) in the range of 50 to 100 rad/s, and
 - $G''(\omega) < G'(\omega)$ at angular frequencies (ω) in the range of 0.01 to 0.05 rad/s.
13. Suspension according to any one of the preceding claims, wherein the suspension has a storage modulus (G') at 0.2 rad/s and 20°C in the range of 1 to 100 Pa.
14. Suspension according to any one of the preceding claims, wherein the suspension has a loss modulus (G'') at 0.2 rad/s and 20°C in the range of 1 to 100 Pa.

15. A packaged detergent product comprising a container and a suspension according to any one of the preceding claims, said container comprising a container wall and an outlet, and said suspension being contained inside the container, wherein at least a part of the container wall is translucent or transparent.

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2017/054722

A. CLASSIFICATION OF SUBJECT MATTER INV. C11D3/20 C11D3/33 C11D3/40 C11D17/00 ADD.		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) C11D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 10 2014 212643 A1 (HENKEL AG & CO KGAA [DE]) 31 December 2015 (2015-12-31) cited in the application paragraphs [0001], [0004] - [0009], [0013], [0016], [0059], [0070], [0080] - [0082]; example 1; table 1 -----	1-15
Y	WO 2015/181570 A1 (RECKITT BENCKISER BRANDS LTD [GB]) 3 December 2015 (2015-12-03) page 1, lines 1-25 page 2, lines 8-21 page 3, line 30 - page 5, line 21 page 10, lines 24-31 page 14, lines 1-7; example 2 ----- -/-	1-15
☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 18 May 2017		Date of mailing of the international search report 29/05/2017
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016		Authorized officer Marttin, Emmeline

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2017/054722

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 2013/160023 A1 (UNILEVER PLC [GB]; UNILEVER NV [NL]; CONOPCO INC DBA UNILEVER [US]) 31 October 2013 (2013-10-31) page 1, lines 11-19 page 4, lines 1-11 page 5, lines 11-14 page 6, line 28 - page 7, line 2 page 21, lines 21-22 page 23, lines 9-18 page 25, line 26; table 5 -----	6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2017/054722

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 102014212643 A1	31-12-2015	DE 102014212643 A1	31-12-2015
		EP 3161117 A1	03-05-2017
		KR 20170024019 A	06-03-2017
		WO 2016000971 A1	07-01-2016

WO 2015181570 A1	03-12-2015	AU 2015265649 A1	05-01-2017
		CA 2950242 A1	03-12-2015
		CN 106414696 A	15-02-2017
		EP 3149141 A1	05-04-2017
		WO 2015181570 A1	03-12-2015

WO 2013160023 A1	31-10-2013	AR 090780 A1	03-12-2014
		CN 104364362 A	18-02-2015
		EP 2841546 A1	04-03-2015
		WO 2013160023 A1	31-10-2013
